

Claims

1. An arrangement for attaching hygienic articles such that their height will be adjustable having
 - 1.1 a wall-mounting rod (1, 21, 31) that
 - 1.1.1 has a continuous, guiding profile for guiding a slide (6) extending over its full length,
 - 1.2 at least one bracket (2, 34) for fastening the wall-mounting rod (1, 21, 31) to a wall or similar that
 - 1.2.1 leaves that part of the guiding profile used for guiding the slide (6) clear.
 2. An arrangement according to claim 1, where the bracket (2, 34) may be attached to the wall-mounting rod (1, 21, 31) in the vicinities of its ends.
 3. An arrangement according to claim 1 or claim 2, where the bracket (2, 34) may be attached to the wall-mounting rod (1, 21, 31) by inserting it into same, latching it onto same, or similar.
 4. An arrangement according to any of the foregoing claims having several, at least partially identically shaped brackets (2, 34).
 5. An arrangement according to any of the foregoing claims, where the at least one bracket (2, 34) is configured for attachment to two sections (1a, 1b, 31a, 31b) of a wall-mounting rod that are to be coaxially arranged.
 6. An arrangement according to any of the foregoing claims, where the at least one bracket (2, 34) has two attachment sections (2a, 2b), one each on or near each of its ends, one (2a) of which is configured for attaching a terminating collar (3) or some other terminating component (4) for terminating the wall-mounting rod.

7. An arrangement according to claim 6, where the attachment section (2a) for attaching the terminating component has a device for the form-fit, or interference-fit, attachment of a terminating component (3, 4).
8. An arrangement according to claims 6 and 7, where both attachment sections (2a, 2b) have means for guiding the sections (1a, 1b, 31a, 31b) of the wall-mounting rod.
9. An arrangement according to any of claims 6 - 8, where the two attachment sections (2a, 2b) are separated by a land (8) that may also form a joint, if desired.
10. An arrangement according to any of the foregoing claims, where the wall-mounting rod (1, 21) has a groove (5), preferably on the front surface of the wall-mounting rod (1, 21), forming a guiding profile.
11. An arrangement according to any of the foregoing claims, where a lower terminating component (4) has an extension of the groove (5).
12. An arrangement according to any of the foregoing claims, where the wall-mounting rod (1, 21) forms a length of hollow, profiled stock and the bracket (2, 34) engages the interior (22) of its hollow profile (1, 21, 31).
13. An arrangement according to any of the foregoing claims, where the accessory items may be attached to the bracket (2, 34, 40), in particular, to the land (8, 41) separating its two attachment sections, where the land may be broadened for this purpose, if necessary.
